

## Republic of the Philippines Department of Agriculture PHILIPPINE FIBER INDUSTRY DEVELOPMENT AUTHORITY



7th Floor Sunnymede IT Center, 1614 Quezon Avenue, Quezon City

## **REQUEST FOR QUOTATION**

The Philippine Fiber Industry Development Authority (PhilFIDA), thru its Bids and Awards Committee (BAC) invites all manufacturers, suppliers and distributors to send their sealed bids/quotations, within seven (7) days from publication hereof, for the supply/delivery of the items enumerated below:

PR NO:         1         1         unit         Fumehood (Ductless type/Branded/Brand New)         275,000.00         PhilFIDA           15-01-049         External size: 1200mmL x 800mmW x 2200mmH         PhilFIDA	CONTRACTO	Item	04	1.1	Description of Home	Approved	Place of
External size: 1200mmL x 800mmW x 2200mmH Internal size: 1082mmL x 755mmW 735mmH with 1 unit 19mm the Solid/homogenous, acid, stain scratch,heat and flame resistant epoxy resin 1 unit acid resistant epoxy resin Durcon greenstone cupsink complete with traps and drainfittings. 1 unit WSF powder coated remote control gooseneck water faucet 1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and allkall resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation władjustable height, 450mm maximum opening Transparent side glass window, to maximize light and visibility inside the cabinet wifoot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant, 300mm diameter inlet diameter with adjustable air speed, 9 levells, air velocity 0.3-0.5 m/s includes re-certification w/ preventive maintenance serni annual P.M. clean interior/exterior of tume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w CE marking On site installation and training	CONTRACTS	No.	Qty.	Unit	Description of Items	Budget(PhP)	Delivery
External size: 1200mmL x 800mmW x 2200mmH Internal size: 1082mmL x 750mmW x 735mmH with 1 unit 19mm this solid/homogenous, acid, stain scratch,heat and flame resistant epoxy resin 1 unit acid resistant epoxy resin Durcon greenstone cupsink complete with traps and drainfittings. 1 unit WSF powder coated remote control gooseneck water faucet 1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet wifloot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M. clean interior/exterior of fume hood, check airlifow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training						,	
External size: 1200mmL x 800mmW x 2200mmH Internal size: 1082mmL x 750mmW x 735mmH with 1 unit 19mm this solid/homogenous, acid, stain scratch,heat and flame resistant epoxy resin 1 unit acid resistant epoxy resin Durcon greenstone cupsink complete with traps and drainfittings. 1 unit WSF powder coated remote control gooseneck water faucet 1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet wifloot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M. clean interior/exterior of fume hood, check airlifow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training	PR NO:	1	1	unit	Fumehood (Ductless type/Branded/Brand New)	275,000.00	PhilFIDA
with 1 unit 1 dym this solid/homogenous, acid, stain scratch,heat and flame resistant epoxy resin 1 unit acid resistant epoxy resin Durcon greenstone cupsink complete with traps and drainfittings. 1 unit WSF powder coated remote control gooseneck water faucet 1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation wadjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet wfloot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification wy preventive maintenance semi annual P.M., clean interior/exterior of furme hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified W CE marking On site installation and training	15-01-049				External size: 1200mmL x 800mmW x 2200mmH		
with 1 unit 19mm thk solid/homogenous, acid, stain scratch,heat and flame resistant epoxy resin 1 unit acid resistant epoxy resin Durcon greenstone cupsink complete with traps and drainfittings. 1 unit WSF powder coated remote control gooseneck water faucet 1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit fam toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window, to maximize light and visibility inside the cabinet w/loot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant, 300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified W CE marking On site installation and training					Internal size: 1082mmL x 750mmW x 735mmH		7/F Sunnymede IT
scratch,heat and flame resistant epoxy resin  1 unit acid resistant epoxy resin Durcon greenstone cupsink complete with traps and drainfittings.  1 unit WSF powder coated remote control gooseneck water faucet  1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector  1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation wladjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of furme hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified W/CE marking On site installation and training					with 1 unit 19mm thk solid/homogenous, acid, stain		
1 unit acid resistant epoxy resin Durcon greenstone cupsink complete with traps and drainfittings. 1 unit WSF powder coated remote control gooseneck water faucet 1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alikali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window, to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant, 300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M. clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test.  ISO & NSF certified w/ CE marking On site installation and training					scratch,heat and flame resistant epoxy resin		Ave., Quezon Ony
cupsink complete with traps and drainfittings.  1 unit WSF powder coated remote control gooseneck water faucet  1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector  1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation władjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/loot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual PM, clean interior/exterior of tume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training							
1 unit WSF powder coated remote control gooseneck water faucet 1 unit WSF powder coated remote control gas spicket 0,40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M. clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training							
spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector  1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch  1 active carbon filter  Micro-processor control system, LCD display  Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing  1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening  Transparent side glass window, to maximize light and visibility inside the cabinet w/foot operated switch  10 degrees slope front ergonomics design, fatigue free working posture  1 unit built-in centrifugal Motor Blower, corrosion resistant, 300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of furne hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test.  ISO & NSF certified w/ CE marking  On site installation and training							
adapter and; 1-surge protector  1 unit WSF powder coated remote control gas spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector  1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant, 300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of furne hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training					·		
spicket 0.40 meters flexible electrical power distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening 1 Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant, 300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training							
distribution system 220V with 2 units universal adapter and; 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant, 300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site Installation and training					•		
adapter and, 1-surge protector 1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P-M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training							
1 unit UV lamp 18w for sterilization and fluorescent lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window, to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training							
lamp 21W-110/220V with light and blower switch 1 active carbon filter Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M. clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training							
1 active carbon filter  Micro-processor control system, LCD display  Cold rolled steel with corrision proof coating exterior casing  High grade melamine board with good acid and alkali  resistance function interior casing  1 unit 5mm toughened motorized front glass window  anti ultraviolet radiation w/adjustable height, 450mm  maximum opening  Transparent side glass window,to maximize light and  visibility inside the cabinet w/foot operated switch  10 degrees slope front ergonomics design, fatigue  free working posture  1 unit built-in centrifugal Motor Blower, corrosion  resistant,300mm diameter inlet diameter with  adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s  Includes re-certification w/ preventive maintenance  semi annual P.M. clean interior/exterior of fume  hood, check airflow alarm system gauge function  check electrical system, verify air velocity & light  intensity test & smoke patern test.  ISO & NSF certified w/ CE marking  On site installation and training					·		
Micro-processor control system, LCD display Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing 1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training					•		
Cold rolled steel with corrision proof coating exterior casing High grade melamine board with good acid and alkali resistance function interior casing  1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M. clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training							
High grade melamine board with good acid and alkali resistance function interior casing  1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening  Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch  10 degrees slope front ergonomics design, fatigue free working posture  1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M., clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test.  ISO & NSF certified w/ CE marking  On site installation and training							
resistance function interior casing  1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening  Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch  10 degrees slope front ergonomics design, fatigue free working posture  1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s  Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test.  ISO & NSF certified w/ CE marking  On site installation and training							
1 unit 5mm toughened motorized front glass window anti ultraviolet radiation w/adjustable height, 450mm maximum opening  Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch  10 degrees slope front ergonomics design, fatigue free working posture  1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test.  ISO & NSF certified w/ CE marking  On site installation and training							
anti ultraviolet radiation w/adjustable height, 450mm maximum opening  Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training					G		
maximum opening Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training					-		
Transparent side glass window,to maximize light and visibility inside the cabinet w/foot operated switch 10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test.  ISO & NSF certified w/ CE marking  On site installation and training							
visibility inside the cabinet w/foot operated switch  10 degrees slope front ergonomics design, fatigue free working posture  1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training					. •		
10 degrees slope front ergonomics design, fatigue free working posture 1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training							
free working posture  1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training					·		
1 unit built-in centrifugal Motor Blower, corrosion resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training							
resistant,300mm diameter inlet diameter with adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training					- 1		
adjustable air speed, 9 levels, air velocity 0.3-0.5 m/s Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training							
Includes re-certification w/ preventive maintenance semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test.  ISO & NSF certified w/ CE marking  On site installation and training					,		
semi annual P.M, clean interior/exterior of fume hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test.  ISO & NSF certified w/ CE marking  On site installation and training							
hood, check airflow alarm system gauge function check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training					·		
check electrical system, verify air velocity & light intensity test & smoke patern test. ISO & NSF certified w/ CE marking On site installation and training							
intensity test & smoke patern test. ISO & NSF certified w/ CE marking  On site installation and training							
ISO & NSF certified w/ CE marking  On site installation and training							
On site installation and training					· · · · · · · · · · · · · · · · · · ·		
one your marranty on parte and correct							
TOTAL 275,000.00						275 000 00	

Interested bidders must be included in the registry of manufacturers/suppliers/ distributors in the PhilGEPS. Price Quotations shall be submitted in a sealed envelope. Information relating to examination, evaluation and comparison of price quotations shall be kept confidential.

Deadline for submission of quotation: 3 July 2015, PhilFIDA, 7th Floor Sunnymede IT Center, 1614 Quezon Avenue, Quezon City.

<u>Please submit your sealed bid / quotation only to the PhilFIDA-BAC Secretariat, addressed to Ms. Marian Joy B. Gray.</u>
For inquiries, please call BAC Secretariat at Telephone No. 441-4081.

ROMEO O. BORDEOS, JR.

BAC. Chairperson

fn: BAC 2014/ RFQ Training Personnel 2014 - TAD PR14-08-594